

HCH-R

**PTFE Teflon® Kevlar® Coated Fiberglass Jointless and Seamless O-rings belt**

**HUI CHENG®** Teflon® PTFE Jointless and Seamless Coated Fiberglass, Kevlar® Fiber and Fiber specialty tapes. Provide excellent release, dimensional stability and high anti-tensile strength Operating temperature range (from -73°C to +260°C), and offer excellent abrasion resistance and excellent resist medicament property resist antistatic applied It is impervious to virtually all chemical attack.

**O-rings belt** Seamless and Jointless of continuously cyclic-running thermal sealing plastic machines packing applications.

**All Kinds of O-rings belt (HCH-R-G- Coated Fiberglass) (HCH-R-K Coated Kevlar® Fibers)**

**HCH-R-G (Coated Fiberglass)**

Type	Girth (mm)	Thickness(mm)
HCH-R-G040	400	0.20
HCH-R-G 056	560	0.20
HCH-R-G 075	750	0.20
HCH-R-G 077	770	0.20
HCH-R-G 081	810	0.20
HCH-R-G 091	910	0.20
HCH-R-G 101	1010	0.20
HCH-R-G 102	1020	0.20
HCH-R-G 127	1270	0.20
HCH-R-G 136	1360	0.20
HCH-R-G 137	1370	0.20
HCH-R-G 150	1500	0.20
HCH-R-G 160	1600	0.20

**HCH-R-K (Coated Kevlar® Fibers)**

Type	Girth (mm)	Thickness(mm)
HCH-R-K040	400	0.25
HCH-R-K 056	560	0.25
HCH-R-K 075	750	0.25
HCH-R-K 077	770	0.25
HCH-R-K 081	810	0.25

HCH-R-K 091	910	0.25
HCH-R-K 101	1010	0.25
HCH-R-K 102	1020	0.25
HCH-R-K 127	1270	0.25
HCH-R-K 136	1360	0.25
HCH-R-K 137	1370	0.25
HCH-R-K 150	1500	0.25
HCH-R-K 160	1600	0.25