

## HCH- F

### HUI CHENG ® Coated Teflon ® PTFE Conveyor Tape

#### HCH- F1

#### HUI CHENG ® Coated Teflon ® PTFE Conveyor Tape

HUI CHENG ® Teflon ® PTFE Seamless or Jointless coated Fiberglass, Kevlar ® Fiber and Nomex ® Fiber specialty tapes

Provide excellent release Teflon ® PTFE Jointless or Seamless coated fabrics, dimensional stability and high anti-tensile strength operating temperature range (from -73°C to +260°C), and offer excellent abrasion resistance and excellent resist medicament property resist antistatic applied It is impervious to virtually all-chemical attack. Seamless or Jointless belt which is laminating machine standard equipment velvet or treating material promise long-life.

Typical Sample Seamless or Jointless Tape Girth (mm)

Seamless or Jointless Teflon ® PTFE Coated Fiberglass Kevlar ® Nomex ® belt Girth (mm)

Standard thickness fabric 14.0~16.0 /mil 0.35~0.40 (mm)									
Width most 60/ in 1500 (mm)									
Seamless or Jointless Girth Tape (mm)									
1360	1380	1440	1470	1510	1520	1530	1540	1550	1560
1580	1600	1640	1660	1680	1730	1740	1780	1820	1830
1840	1850	1870	1880	1950	2000	2040	2100	2230	2240
2250	2310	2320	2420	2440	2450	2500	2600	2630	2750
2800	2820	2850	2880	2900	3050	3080	3090	3200	3450
3540	3590	3820	3850	3890	3900	3920	3930	4200	4270
5100	5270	5400	5640	5800	6000	6440	6700		