

HCH-A-T

Teflon film tape

Specialty of tape

HUI CHENG ® specialty manufactures sintered PTFE Teflon ® skived film, is used as wire and cable barrier and insulation tapes as well as convoluted hose walls. Demanding gaskets, Low coefficient of friction excellent, thicker skived PTFE film is used as a bearing material. Sintered PTFE skived films, have higher tensile strength, specific coefficient of friction, Outstanding nonstick performance, Resistance chemical properties, operating temperature range (from -73°C to +280°C),

Type	thickness (mm)	Max width(mm)	Operating temperature ()	tensile strength kgf/cm2	Elongation rate%
HCH-A-T 030	0.030	120	260	140~350	300
HCH-A-T 050	0.050	400	260	140~350	300
HCH-A-T 080	0.080	400	260	140~350	300
HCH-A-T 100	0.100	400	260	140~350	300
HCH-A-T 130	0.130	500	260	140~350	300
HCH-A-T 150	0.150	500	260	140~350	300
HCH-A-T 180	0.180	700	260	140~350	300
HCH-A-T 200	0.200	700	260	140~350	300
HCH-A-T 250	0.250	800	260	140~350	300
HCH-A-T 300	0.300	1000	260	140~350	300
HCH-A-T 400	0.400	1000	260	140~350	300
HCH-A-T 500	0.500	1000	260	140~350	300
HCH-A-T 600	0.600	1000	260	140~350	300
HCH-A-T 700	0.700	1000	260	140~350	300
HCH-A-T 800	0.800	1000	260	140~350	300
HCH-A-T 900	0.900	1000	260	140~350	300
HCH-A-T 1000	1.000	1500	260	140~350	300
HCH-A-T 2000	2.000	1500	260	140~350	300
HCH-A-T 3000	3.000	1500	260	140~350	300